

### General Description

The MIC39300, MIC39301 and MIC39302 are 3.0A low-dropout linear voltage regulators that provide a low voltage, high-current output with a minimum of external components. Utilizing Micrel's proprietary Super  $\beta$  PNP<sup>®</sup> pass element, the MIC39300/1/2 offers extremely low dropout (typically 385mV at 3.0A) and low ground current (typically 36mA at 3.0A).

The MIC39300/1/2 is ideal for PC add-in cards that need to convert from standard 3.3V to 2.5V or 2.5V to 1.8V. A guaranteed maximum dropout voltage of 500mV over all operating conditions allows the MIC39300/1/2 to provide 2.5V from a supply as low as 3V, and 1.8V from a supply as low as 2.5V. The MIC39300/1/2 also has fast transient response for heavy switching applications. The device requires only 47 $\mu$ F of output capacitance to maintain stability and achieve fast transient response.

The MIC39300/1/2 is fully protected with overcurrent limiting, thermal shutdown, reversed-battery protection, reversed-leakage protection, and reversed-lead insertion. The MIC39301 offers a TTL-logic compatible enable pin and an error flag that indicates under voltage and over current conditions. Offered in fixed voltages, the MIC39300/1 comes in the TO-220 and TO-263 (D<sup>2</sup>Pak) packages and is an ideal upgrade to older, NPN-based linear voltage regulators. The MIC39302 adjustable option allows programming the output voltage anywhere between 1.24V and 15.5V and is offered in a 5-Pin, TO-263 (D<sup>2</sup>Pak) package.


### Features

- 3.0A minimum guaranteed output current
- 550mV maximum dropout voltage over temperature
- Ideal for 3.0V to 2.5V conversion
- Ideal for 2.5V to 1.8V conversion
- 1% initial accuracy
- Low ground current
- Current limiting and Thermal shutdown
- Reversed-battery protection
- Reversed-leakage protection
- Fast transient response
- TO-263 (D<sup>2</sup>Pak) and TO-220 packaging
- TTL/CMOS compatible enable pin (MIC39301/2 only)
- Error flag output (MIC39301 only)
- Adjustable output (MIC39302 only)


### Applications

- LDO linear regulator for PC add-in cards
- High-efficiency linear power supplies
- SMPS post regulator
- Multimedia and PC processor supplies
- Low-voltage microcontrollers
- StrongARM<sup>™</sup> processor supply


### Typical Application



MIC39300



MIC39301



MIC39302 Adjustable Output Application  
(\*See Minimum Load Current Section)

Super  $\beta$  PNP is a registered trademark of Micrel, Inc.  
StrongARM is a trademark of Advanced RISC Machines, Ltd

\*\*See Thermal Load Current Section


## Ordering Information

| Part Number    |                 | Voltage    | Junction Temp Range | Package      |
|----------------|-----------------|------------|---------------------|--------------|
| Standard       | RoHS Compliant* |            |                     |              |
| MIC39300-1.8BT | MIC39300-1.8WT  | 1.8V       | -40°C to +125°C     | 3-Pin TO-220 |
| MIC39300-1.8BU | MIC39300-1.8WU  | 1.8V       | -40°C to +125°C     | 3-Pin TO-263 |
| MIC39300-2.5BT | MIC39300-2.5WT  | 2.5V       | -40°C to +125°C     | 3-Pin TO-220 |
| MIC39300-2.5BU | MIC39300-2.5WU  | 2.5V       | -40°C to +125°C     | 3-Pin TO-263 |
| MIC39301-1.8BT | MIC39301-1.8WT  | 1.8V       | -40°C to +125°C     | 5-Pin TO-220 |
| MIC39301-1.8BU | MIC39301-1.8WU  | 1.8V       | -40°C to +125°C     | 5-Pin TO-263 |
| MIC39301-2.5BT | MIC39301-2.5WT  | 2.5V       | -40°C to +125°C     | 5-Pin TO-220 |
| MIC39301-2.5BU | MIC39301-2.5WU  | 2.5V       | -40°C to +125°C     | 5-Pin TO-263 |
| —              | MIC39302WU      | Adjustable | -40°C to +125°C     | 5-Pin TO-263 |


**Note:**

\* RoHS compliant with 'high-melting solder' exemption.


## Pin Configuration




**MIC39300-x.xBT  
TO-220-3 (T)**




**MIC39300-x.xBU  
TO-263-3 (U)**



**MIC39301-x.xBT  
TO-220-5 (T)**



**MIC39301-x.xBU  
TO-263-5 (D<sup>2</sup>Pak) (U)**



**MIC39302WU  
TO-263-5 (D<sup>2</sup>Pak) (U)**

## Pin Description

| Pin Number<br>MIC39300 | Pin Number<br>MIC39301 | Pin Number<br>MIC39302 | Pin Name | Pin Function  |
|------------------------|------------------------|------------------------|----------|---|
| —                      | 1                      | 1                      | EN       | Enable (Input): TTL/CMOS compatible input. Logic high = enable; logic low or open = shutdown.   |
| 1                      | 2                      | 2                      | IN       | Unregulated Input: +16V maximum supply.   |
| 2, TAB                 | 3, TAB                 | 3, TAB                 | GND      | Ground: Ground pin and TAB are internally connected.  |
| 3                      | 4                      | 4                      | OUT      | Regulator Output  |
| —                      | 5                      | —                      | FLG      | Error Flag (Output): Open-collector indicates an output fault condition. Active low.  |
| —                      | —                      | 5                      | ADJ      | Adjustable Regulator Feedback Input: Connect to the resistor voltage divider that is placed from OUT to GND in order to set the output voltage. |

**Absolute Maximum Ratings<sup>(1)</sup>**

|                                 |                      |
|---------------------------------|----------------------|
| Supply Voltage ( $V_{IN}$ )     | –20V to +20V         |
| Enable Voltage ( $V_{EN}$ )     | +20V                 |
| Storage Temperature ( $T_S$ )   | –65°C to +150°C Lead |
| Temperature (soldering, 5 sec.) | 260°C                |
| ESD Rating                      | <b>Note 3</b>        |

**Operating Ratings<sup>(2)</sup>**

|  |                 |
|--|-----------------|
| Supply Voltage ( $V_{IN}$ )                | +2.5V to +16V   |
| Enable Voltage ( $V_{EN}$ )                | +16V            |
| Maximum Power Dissipation ( $P_{D(max)}$ ) | <b>Note 4</b>   |
| Junction Temperature ( $T_J$ )             | –40°C to +125°C |
| Package Thermal Resistance                 |                 |
| TO-263 ( $\theta_{JC}$ )                   | 2°C/W           |
| TO-220 ( $\theta_{JC}$ )                   | 2°C/W           |

**Electrical Characteristics<sup>(5)</sup>**

$T_J = 25^\circ\text{C}$ , **bold** values indicate  $-40^\circ\text{C} \leq T_J \leq +125^\circ\text{C}$ , unless noted.

| Symbol                    | Parameter   | Condition  | Min | Typ  | Max | Units  |
|---------------------------|---|--|-----|------|-----|--------|
| $V_{OUT}$                 | Output Voltage                                    | 10mA   | –1  |      | 1   | %      |
|                           |   | $10\text{mA} \leq I_{OUT} \leq 3\text{A}$ , $V_{OUT} + 1\text{V} \leq V_{IN} \leq 8\text{V}$ | –2  |      | 2   | %      |
|                           | Line Regulation                                   | $I_{OUT} = 10\text{mA}$ , $V_{OUT} + 1\text{V} \leq V_{IN} \leq 8\text{V}$                   |     | 0.06 | 0.5 | %      |
|                           | Load Regulation                                   | $V_{IN} = V_{OUT} + 1\text{V}$ , $10\text{mA} \leq I_{OUT} \leq 3\text{A}$                   |     | 0.2  | 1   | %      |
| $\Delta V_{OUT}/\Delta T$ | Output Voltage Temp. Coefficient<br><b>Note 6</b> |  |     | 20   | 100 | ppm/°C |
| $V_{DO}$                  | Dropout Voltage<br><b>Note 7, Note 10</b>         | $I_{OUT} = 100\text{mA}$ , $\Delta V_{OUT} = -1\%$   |     | 65   | 200 | mV     |
|                           |   | $I_{OUT} = 750\text{mA}$ , $\Delta V_{OUT} = -1\%$   |     | 185  |     | mV     |
|                           |   | $I_{OUT} = 1.5\text{A}$ , $\Delta V_{OUT} = -1\%$  |     | 250  |     | mV     |
|                           |   | $I_{OUT} = 3\text{A}$ , $\Delta V_{OUT} = -1\%$  |     | 385  | 550 | mV     |
| $I_{GND}$                 | Ground Current<br><b>Note 8</b>                   | $I_{OUT} = 750\text{mA}$ , $V_{IN} = V_{OUT} + 1\text{V}$                                    |     | 10   | 20  | mA     |
|                           |   | $I_{OUT} = 1.5\text{A}$ , $V_{IN} = V_{OUT} + 1\text{V}$                                     |     | 17   |     | mA     |
|                           |   | $I_{OUT} = 3\text{A}$ , $V_{IN} = V_{OUT} + 1\text{V}$                                       |     | 45   |     | mA     |
| $I_{GND(do)}$             | Dropout Ground Pin Current                        | $V_{IN} \leq V_{OUT(nominal)} - 0.5\text{V}$ , $I_{OUT} = 10\text{mA}$                       |     | 6    |     | mA     |
| $I_{OUT(lim)}$            | Current Limit                                     | $V_{OUT} = 0\text{V}$ , $V_{IN} = V_{OUT} + 1\text{V}$                                       |     | 4.5  |     | A      |

**Enable Input (MIC39301)**

|                 |                         |                        |     |    |     |               |
|-----------------|-------------------------|------------------------|-----|----|-----|---------------|
| $V_{EN}$        | Enable Input Voltage    | logic low (off)        |     |    | 0.8 | V             |
|                 |                         | logic high (on)        | 2.5 |    |     | V             |
| $I_{IN}$        | Enable Input Current    | $V_{EN} = 2.5\text{V}$ |     | 15 | 30  | $\mu\text{A}$ |
|                 |                         |                        |     |    | 75  | $\mu\text{A}$ |
|                 |                         | $V_{EN} = 0.8\text{V}$ |     |    | 2   | $\mu\text{A}$ |
|                 |                         |                        |     |    | 4   | $\mu\text{A}$ |
| $I_{OUT(shdn)}$ | Shutdown Output Current | <b>Note 9</b>          |     | 10 | 20  | $\mu\text{A}$ |

**Flag Output (MIC39301)**













|                 |                        |   |    |      |      |               |
|-----------------|------------------------|---|----|------|------|---------------|
| $I_{FLG(leak)}$ | Output Leakage Current | $V_{OH} = 16\text{V}$   |    | 0.01 | 1    | $\mu\text{A}$ |
|                 |                        |   |    |      | 2    | $\mu\text{A}$ |
| $V_{FLG(do)}$   | Output Low Voltage     | $V_{IN} = 2.5\text{V}$ , $I_{OL} = 250\mu\text{A}$ , <b>Note 10</b> |    | 220  | 300  | mV            |
|                 |                        |   |    |      | 400  | mV            |
| $V_{FLG}$       | Low Threshold          | % of $V_{OUT}$  | 93 |      |      | %             |
|                 | High Threshold         | % of $V_{OUT}$  |    |      | 99.2 | %             |
|                 | Hysteresis             |   |    | 1    |      | %             |

| Symbol  | Parameter                                 | Condition      | Min          | Typ   | Max          | Units  |
|---|---|----------------|--------------|-------|--------------|--------|
| <b>Reference (Adjust Pin) – MIC39302 only</b> |   |                |              |       |              |        |
| V <sub>ADJ</sub>                              | Reference Voltage                         |                | 1.228        | 1.240 | 1.252        | V      |
|   |   |                | <b>1.215</b> |       | <b>1.265</b> | V      |
| V <sub>TC</sub>                               | Reference Voltage Temp. Coefficient       | <b>Note 11</b> |              | 20    |              | ppm/°C |
| I <sub>ADJ</sub>                              | Adjust Pin Bias Current                   |                |              | 40    | 80           | nA     |
|   |   |                |              |       | <b>120</b>   | nA     |
| I <sub>TC</sub>                               | Adjust Pin Bias Current Temp. Coefficient |                |              | 0.1   |              | nA/°C  |





**Notes:**

- Exceeding the absolute maximum ratings may damage the device.
- The device is not guaranteed to function outside its operating rating.
- Devices are ESD sensitive. Handling precautions recommended.
- $P_{D(max)} = (T_{J(max)} - T_A) \div \theta_{JA}$ , where  $\theta_{JA}$  depends upon the printed circuit layout. See "Applications Information."
- Specification for packaged product only.
- Output voltage temperature coefficient is  $\Delta V_{OUT(worst\ case)} \div (T_{J(max)} - T_{J(min)})$  where  $T_{J(max)}$  is +125°C and  $T_{J(min)}$  is -40°C.
- $V_{DO} = V_{IN} - V_{OUT}$  when  $V_{OUT}$  decreases to 99% of its nominal output voltage with  $V_{IN} = V_{OUT} + 1V$ . For output voltages below 2.5V, dropout voltage is the input-to-output voltage differential with the minimum input voltage being 2.5V. Minimum input operating voltage is 2.5V.
- I<sub>GND</sub> is the quiescent current.  $I_{IN} = I_{GND} + I_{OUT}$ .
- $V_{EN} \leq 0.8V$ ,  $V_{IN} \leq 8V$ , and  $V_{OUT} = 0V$
- For a 1.8V device,  $V_{IN} = 2.5V$ .
- Thermal regulation is defined as the change in output voltage at a time t after a change in power dissipation is applied, excluding load or line regulation effects. Specifications are for a 200mA load pulse at  $V_{IN} = 8V$  for t = 10ms.




# Typical Characteristics



### Typical Characteristics (cont)




## Functional Characteristics





### Functional Diagram



\* MIC39301 only

## Application Information

The MIC39300/1/2 are high-performance, low-dropout voltage regulators suitable for moderate to high-current voltage regulator applications. Its 550mV dropout voltage at full load makes it especially valuable in battery-powered systems and as a high-efficiency noise filter in post-regulator applications. Unlike older NPN-pass transistor designs, where the minimum dropout voltage is limited by the base-to-emitter voltage drop and collector-to-emitter saturation voltage, dropout performance of the PNP output of these devices is limited only by the low  $V_{CE}$  saturation voltage.

A trade-off for the low dropout voltage is a varying base drive requirement. Micrel's Super  $\beta$  PNP<sup>®</sup> process reduces this drive requirement to only 2% to 5% of the load current.

The MIC39300/1/2 regulators are fully protected from damage due to fault conditions. Current limiting is provided. This limiting is linear; output current during overload conditions is constant. Thermal shutdown disables the device when the die temperature exceeds the maximum safe operating temperature. Transient protection allows device (and load) survival even when the input voltage spikes above and below nominal. The output structure of these regulators allows voltages in excess of the desired output voltage to be applied without reverse current flow.

### Thermal Design

Linear regulators are simple to use. The most complicated design parameters to consider are thermal characteristics. Thermal design requires four application-specific parameters:

- Maximum ambient temperature ( $T_A$ )
- Output Current ( $I_{OUT}$ )
- Output Voltage ( $V_{OUT}$ )
- Input Voltage ( $V_{IN}$ )
- Ground Current ( $I_{GND}$ )

Calculate the power dissipation of the regulator from these numbers and the device parameters from this datasheet, where the ground current is taken from the data sheet.

$$P_D = (V_{IN} - V_{OUT}) I_{OUT} + V_{IN} \times I_{GND}$$

The heat sink thermal resistance is determined by:

$$\theta_{SA} = \frac{T_{J(max)} - T_A}{P_D} - (\theta_{JC} + \theta_{CS})$$

where  $T_{J(max)} \leq 125^\circ\text{C}$  and  $\theta_{CS}$  is between  $0^\circ$  and  $2^\circ\text{C/W}$ .

The heat sink may be significantly reduced in applications where the minimum input voltage is known and is large compared with the dropout voltage. Use a series input resistor to drop excessive voltage and

distribute the heat between this resistor and the regulator. The low dropout properties of Micrel Super  $\beta$  PNP<sup>®</sup> regulators allow significant reductions in regulator power dissipation and the associated heat sink without compromising performance. When this technique is employed, a capacitor of at least  $1.0\mu\text{F}$  is needed directly between the input and regulator ground.

Refer to "Application Note 9" for further details and examples on thermal design and heat sink specification.




Figure 1. Capacitor Requirements

### Output Capacitor

The MIC39300/1/2 requires an output capacitor to maintain stability and improve transient response. Proper capacitor selection is important to ensure proper operation. The MIC39300/1/2 output capacitor selection is dependent upon the ESR (equivalent series resistance) of the output capacitor to maintain stability. When the output capacitor is  $47\mu\text{F}$  or greater, the output capacitor should have less than  $1\Omega$  of ESR. This will improve transient response as well as promote stability. Ultralow ESR capacitors, such as ceramic chip capacitors may promote instability. These very low ESR levels may cause an oscillation and/or underdamped transient response. A low-ESR solid tantalum capacitor works extremely well and provides good transient response and stability over temperature. Aluminum electrolytics can also be used, as long as the ESR of the capacitor is  $< 1\Omega$ .

The value of the output capacitor can be increased without limit. Higher capacitance values help to improve transient response and ripple rejection and reduce output noise.

### Input Capacitor

An input capacitor of  $1\mu\text{F}$  or greater is recommended when the device is more than 4 inches away from the bulk ac supply capacitance, or when the supply is a battery. Small, surface mount, ceramic chip capacitors can be used for the bypassing. Larger values will help to improve ripple rejection by bypassing the input to the regulator, further improving the integrity of the output voltage.

### Transient Response and 3.3V to 2.5V and 2.5V to 1.8V Conversions

The MIC39300/1/2 has excellent transient response to variations in input voltage and load current. The device has been designed to respond quickly to load current variations and input voltage variations. Large output capacitors are not required to obtain this performance. A standard 47 $\mu$ F output capacitor, preferably tantalum, is all that is required. Larger values help to improve performance even further.

By virtue of its low-dropout voltage, this device does not saturate into dropout as readily as similar NPN-based designs. When converting from 3.3V to 2.5V or 2.5V to 1.8V, the NPN-based regulators are already operating in dropout, with typical dropout requirements of 1.2V or greater. To convert down to 2.5V without operating in dropout, NPN-based regulators require an input voltage of 3.7V at the very least. The MIC39300/1 regulator will provide excellent performance with an input as low as 3.0V or 2.5V. This gives the PNP-based regulators a distinct advantage over older, NPN-based linear regulators.

### Minimum Load Current

The MIC39300/1/2 regulators are specified between finite loads. If the output current is too small, leakage currents dominate and the output voltage rises. A 10mA minimum load current is necessary for proper regulation.

### Error Flag

The MIC39301 version features an error flag circuit which monitors the output voltage and signals an error condition when the voltage drops 5% below the nominal output voltage. The error flag is an open-collector output that can sink 10mA during a fault condition.


Low output voltage can be caused by a number of problems, including an overcurrent fault (device in current limit) or low input voltage. The flag is inoperative during overtemperature shutdown.

When the error flag is not used, it is best to leave it open. A pull-up resistor from FLG to either  $V_{IN}$  or  $V_{OUT}$  is required for proper operation.

### Enable Input

The MIC39301/2 features an enable input for on/off control of the device. The enable input's shutdown state draws "zero" current (only microamperes of leakage). The enable input is TTL/CMOS compatible for simple logic interface, but can be connected to up to 20V. When enabled, it draws approximately 15 $\mu$ A.

### Adjustable Regulator Design




**Figure 2. Adjustable Regulator with Resistors**

The MIC39302 allows programming the output voltage anywhere between 1.24V and 15.5V. Two resistors are used. The resistor values are calculated by:


$$R1 = R2 \times \left(\frac{V_{OUT}}{1.240} - 1\right)$$

Where  $V_{OUT}$  is the desired output voltage. Figure 2 shows component definition. Applications with widely varying load currents may scale the resistors to draw the minimum load current required for proper operation (see *Minimum Load Current* section).


### Package Information




3-Pin TO-220 (T)



5-Pin TO-220 (T)



**3-Pin TO-263 (U)**



**5-Pin TO-263 (U)**

**MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA**  
 TEL +1 (408) 944-0800 FAX +1 (408) 474-1000 WEB <http://www.micrel.com>

The information furnished by Micrel in this data sheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is a Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2009 Micrel, Incorporated.