



Spiral Wrap Plastic Tubing For Harnesses

Available from four materials: Polyethylene, Rulan (flame retardant Polyethylene), Nylon and Teflon. These insulations are easily applied by twisting them over the item(s) to be protected. They can be flexed repeatedly without cracking or breaking. Spiral Wrap is reuseable and expandable. It bends around sharp corners. Per MIL-P-21922B, MIL-I-631D, MIL-P-3803.

Cut lengths are available.

Polyethylene This series is RoHS compliant.		Temp. Range: -105°F to +200°F			
Daburn Cat. No.		Covers Wire Groups	Outside Diameter	Nom. Wall	Standard Package
Natural	Black				
605-1/8	605B-1/8	1/16" to 1/2"	1/8"	.031"	100', 500', 1000'
605-1/4	605B-1/4	3/16" to 2"	1/4"	.045"	100', 500', 1000'
605-3/8	605B-3/8	5/16" to 3"	3/8"	.058"	100', 500', 1000'
605-1/2	605B-1/2	3/4" to 4"	1/2"	.058"	100', 500', 1000'
Rulan (White) This series is RoHS compliant.		Temp. Range: -10°F to +200°F			
Daburn Cat. No.		Covers Wire Groups	Outside Diameter	Nom. Wall	Standard Package
606-1/8		1/16" to 1/2"	1/8"	.030"	100', 500', 1000'
606-1/4		3/16" to 1 1/2"	1/4"	.045"	100', 500', 1000'
606-3/8		5/16" to 2"	3/8"	.052"	100', 500', 1000'
606-1/2		3/4" to 4"	1/2"	.062"	100', 500', 1000'

Nylon Per MIL-P-22692, MIL-I-20693, MIL-M-22096, MIL-M-19098 This series is RoHS compliant.		Temp. Range: -212°F to +300°F			
--	--	--------------------------------------	--	--	--

Daburn Cat. No.		Covers Wire Groups	Outside Diameter	Nom. Wall	Standard Package
Natural	Black				
607-1/8	607B-1/8	1/16" to 1/2"	1/8"	.030"	100', 500', 1000'
607-1/4	607B-1/4	3/16" to 2"	1/4"	.025"	100', 500', 1000'
607-3/8	607B-3/8	5/16" to 3"	3/8"	.035"	100', 500', 1000'
607-1/2	607B-1/2	3/4" to 4"	1/2"	.035"	100', 500', 1000'

Teflon (Natural) Per MIL-I-22129, MIL-T-47287A, AMS-3653 This series is RoHS compliant.		Temp. Range: -450°F to +500°F			
--	--	--------------------------------------	--	--	--

Daburn Cat. No.		Covers Wire Groups	Outside Diameter	Nom. Wall	Standard Package
608-1/8					
608-1/4		3/16" to 2"	1/4"	.030"	100', 500'
608-3/8		5/16" to 3"	3/8"	.030"	100', 500'
608-1/2		3/4" to 3"	1/2"	.030"	100', 500'
608-3/4		11/16" to 6"	3/4"	.040"	100', 200'
608-1"		15/16" to 8"	1"	.040"	100', 200'

To [Additional insulating Tubing and Sleeving](#)

Back to DABURN'S [Home Page](#)

Daburn electronics & cable corp.

224 Pegasus Ave.

Northvale, NJ 07647-1909

Tel: 201-768-5400

Fax: 201-768-9642

E-Mail: daburn@daburn.com

URL: <http://www.daburn.com>