ſ	T G	т п	D	0	₩ 2	Þ				
4	M Thread	ØF F F F F F F F F F F F F F F F F F F					4			
ယ				LAYOUT SHOWN AS EX	XAMPLE		3			
		Keying Shown as example								
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal	7							
2	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum	F25.4 MaxZ31.5 MaxVV THREADM22x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed						
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D115	-05SN					
	-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours		A 27	-09-2016 First Release						
			ISS Designed B	DATE Latest modification - by y: Date:	CUSTOMER DRAWIN	MOD N°				
			тіт	rLE Aluminium	n Inline plug 8D series					
<u> </u>	BASIC SERIES:8D1-15FSHELL TYPE: In line Receptacle </td <td>05 S N</td> <td>SCALE NA NTATION : N</td> <td>General linear Tolerances: ±</td> <td>NPRDS / PROJECT 859 This document is the SOURIAU</td> <td></td> <td>1</td>	05 S N	SCALE NA NTATION : N	General linear Tolerances: ±	NPRDS / PROJECT 859 This document is the SOURIAU		1			
	SHELL SIZE : 15	CONTACT TYPE : SOCKET(5	500 Matings)	RIAU WWW.SOURIAU.C	CIVI it must not be represented without					
	PLATING : F = Nickel	CONTACT LAY	YOUT : 15-05	SOURIAU 8D115F0		SHEET 1/2				
L	H G	F E	D	C	B	Α				

ſ		т		Q	т	ш		D	0		I	₩	A		
4			Contact (insert arrangem Contact position ID X-axis (mm) A +.000 (0.00	⊕ ⊕ c t 15-5) ocation Y-axis (mm) +.100 (2.54)											4
		Shell Arrangeme size no. 15 -5	C +.094 (2.39 D 094 (2.39 E 174 (4.42 ant Number of contacts	148 (3.76) +.024 (0.61) Service Contact Su rating location											
ယ															3
									SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
N										PN: 8D	Country FR 115F05	Jurisdiction & Control List Not Listed			2
								A 27-09-20 ISS DATE	016 First Release	cation - by				MOD N°	
								Designed By:	D	Date: CUSTOMER DRAWING Aluminium Inline plug 8D series					
<u>→</u>								SCALE NA		General Tolerar ±	nces:	NPRDS / PROJEC 859 This document is t		y of	1
								SOURIA	U ww	W.SOURI		SOURI, it must not be re communicated with	\U produced	or ssion	
							I	A3			IAU DR 15F05S			SHEET 2/2	
l	L	Н		G	F	Е		D	C			B	Α		l