

## Lightning arrester type 1 - FLT 100 N/PE CTRL-1.5 - 2856388

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Lightning current arrester with encapsulated N-PE spark gap and ignition electronics, 1-channel. Protection level: 1.5 kV. Housing width: 35 mm (2 Div.)



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	318.7 GRM
Custom tariff number	85363030
Country of origin	Germany

### Technical data

#### Dimensions

Height	90 mm
Width	35.8 mm
Depth	65.7 mm
Horizontal pitch	2 Div.

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Permissible humidity (operation)	≤ 95 %

#### General

IEC power supply system	TT
	TN-S
Housing material	PBT
Inflammability class according to UL 94	V0
Color	black
Standards for air and creepage distances	EN 60664-1

# Lightning arrester type 1 - FLT 100 N/PE CTRL-1.5 - 2856388

## Technical data

### General

	EN61643-11
Mounting type	DIN rail: 35 mm
Type	Rail-mountable module, one-piece
Surge protection fault message	None
Direction of action	N-PE

### Protective circuit

IEC test classification	I
	T1
EN type	T1
Nominal voltage $U_N$	230 V AC (400 V AC / TN, TT)
Maximum continuous operating voltage $U_C$	260 V AC
Maximum continuous operating voltage $U_C$ (N-PE)	260 V AC
$U_T$ (TOV-safe)	1200 V AC (200 ms)
Nominal frequency $f_N$	50 Hz
	60 Hz
Residual current $I_{PE}$	$\leq 0.1$ mA
Standby power consumption $P_C$	$\leq 26$ mVA
Max. discharge current $I_{max}$ (8/20) $\mu$ s	100 kA
Max. discharge current $I_{max}$ (8/20) $\mu$ s maximum (N-PE)	100 kA
Nominal discharge current $I_n$ (8/20) $\mu$ s	100 kA
Nominal discharge current $I_n$ (8/20) $\mu$ s (N-PE)	100 kA
Impulse discharge current (10/350) $\mu$ s charge	50 As
Impulse discharge current (10/350) $\mu$ s, specific energy	3 MJ/ $\Omega$
Impulse discharge current (10/350) $\mu$ s, peak value $I_{imp}$	100 kA
Front of wave sparkover voltage at 6 kV (1.2/50) $\mu$ s	$\leq 1.5$ kV
Front of wave sparkover voltage at 6 kV (1.2/50) $\mu$ s (N-PE)	$\leq 1.5$ kV
Voltage protection level $U_p$	$\leq 1.5$ kV
Voltage protection level $U_p$ (N-PE)	$\leq 1.5$ kV
Response time	$\leq 100$ ns
Response time (N-PE)	$\leq 100$ ns
Follow current quenching capacity $I_f$	100 A
Follow current quenching capacity $I_f$ (N-PE)	100 A

### Connection, protective circuit

Connection method	Screw connection
Connection type IN	Biconnect screw terminal block
Connection type OUT	Biconnect screw terminal block

# Lightning arrester type 1 - FLT 100 N/PE CTRL-1.5 - 2856388

## Technical data

### Connection, protective circuit

Connection method	Biconnect terminal block
Screw thread	M6
Tightening torque	8 Nm
Stripping length	19 mm
Conductor cross section stranded min.	16 mm <sup>2</sup>
Conductor cross section stranded max.	35 mm <sup>2</sup>
Conductor cross section solid min.	10 mm <sup>2</sup>
Conductor cross section solid max.	50 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	6
Conductor cross section AWG/kcmil max	1

### Standards and Regulations

Standards/regulations	IEC 61643-1 2005
	DIN EN 61643-11 2002
	DIN EN 61643-11/A11 2007

## Classifications

### eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27140201
eCl@ss 5.0	27140201
eCl@ss 5.1	27140201
eCl@ss 6.0	27140201
eCl@ss 7.0	27140201
eCl@ss 8.0	27140201

### ETIM

ETIM 2.0	EC000381
ETIM 3.0	EC000381
ETIM 4.0	EC000381
ETIM 5.0	EC000381

### UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610

# Lightning arrester type 1 - FLT 100 N/PE CTRL-1.5 - 2856388

## Classifications

UNSPSC

UNSPSC 13.2	39121620
-------------	----------

## Approvals

Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted


---

## Approval details


GOST
------

## Drawings

Dimensioned drawing



Circuit diagram



## Lightning arrester type 1 - FLT 100 N/PE CTRL-1.5 - 2856388

Catalog photo




Figure may contain other products.

---

Phoenix Contact 2014 © - all rights reserved  
<http://www.phoenixcontact.com>