



P.C. BOARD DETAIL

SPECIFICATIONS:

INSULATING BODY: PA 68 UL 94 VO (GREEN)
 CONTACTS: CuZn37 + Ni + Sn
 NOMINAL CURRENT: 6.3A
 RATED VOLTAGE: 250V

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS.
 DIMENSIONS IN BRACKETS [] ARE INCHES
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

CPK DENOTES CRITICAL CHARACTERISTICS.
 CPK DENOTES CPK DIMENSIONS - MINIMUM CPK VALUE

ST DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE IN ACCORDANCE WITH THE MEASUREMENT PROCEDURE SPECIFIED IN THE INSTRUCTIONS.
 ST DENOTES ST DIMENSIONS - MINIMUM CP VALUE

CPK AND ST DIMENSIONS MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SPECIFIED IN THE INSTRUCTIONS AND MUST BE FULLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

UNCONTROLLED DOCUMENT

NO		COMPONENT NO	DESCRIPTION	QTY/M	U/M
BILL OF MATERIAL					
CDPLIES TO		MATERIAL SPEC		FINISH	
LTR	REVISION				
A	61471 - RELEASED 6/4/04	BJJ	SCALE 2:1	DATE 06/09/04	SUPER DRW
B	83902D - CHG. COLOR OF BODY TO BLACK	BJJ	DATE	DATE	FINISH GOOD WT
C	84064D-CHG BLACK TO GREEN 12/15/04 PJM	BJJ	APPD	DATE	GRAMS/PIECE
TOLERANCE UNLESS OTHERWISE SPECIFIED TWO PLACE DEC +.25(-.01) FRACTION ± THREE PLACE DEC ±.100(-.004) ANGULAR ±1°					
TITLE 5 X 20mm PC BOARD FUSEHOLDER					
3RD ANGLE PROJECTION					
		DES PLAINES, ILLINOIS 60018		DRAWN NO. OPTF0075P FINAL	