




DESCRIPTION: CAT5E ASSEMBLED PATCH CABLE
 MODEL NUMBER: 73-777X-XXX
 APPLICATION: PATCH CABLE
 CRIMP TOOL: N/A
 IMPEDANCE: N/A
 TEMPERATURE RANGE: 0 ~ 75 DEG C
 MATERIAL: PLUG RJ-45, GOLD PLATED ON CONTACTS
 CABLE UTP, 24 AWG, 4 TWISTED PAIRS, STRANDED BARE COPPER,
 UL ETL EIA/TIA-568B VERIFIED CATEGORY 5E
 RoHS COMPLIANCE: YES
 TECHNICAL DETAIL: N/A



PIN ASSIGNMENT	
	P1 P2
WHITE/ORANGE	1 1
ORANGE	2 2
WHITE/GREEN	3 3
GREEN	6 6
BLUE	4 4
WHITE/BLUE	5 5
WHITE/BROWN	7 7
BROWN	8 8

X=COLOR
 0-GRAY
 1-BLACK
 2-BLUE
 3-GREEN
 4-RED
 5-YELLOW
 6-WHITE
 7-ORANGE
 8-PINK
 9-PURPLE

TABLE 1

MODEL NUMBER	LENGTH (FEET)	DESCRIPTION
73-777X-1	1	CATE 5E ASSEMBLED PATCH CABLE , 1FT
73-777X-3	3	CATE 5E ASSEMBLED PATCH CABLE , 3FT
73-777X-5	5	CATE 5E ASSEMBLED PATCH CABLE , 5FT
73-777X-7	7	CATE 5E ASSEMBLED PATCH CABLE , 7FT
73-777X-10	10	CATE 5E ASSEMBLED PATCH CABLE , 10FT
73-777X-14	14	CATE 5E ASSEMBLED PATCH CABLE , 14FT
73-777X-25	25	CATE 5E ASSEMBLED PATCH CABLE , 25FT
73-777X-50	50	CATE 5E ASSEMBLED PATCH CABLE , 50FT
73-777X-100	100	CATE 5E ASSEMBLED PATCH CABLE , 100FT

		AIM-Cambridge	
	RoHS2 <input checked="" type="checkbox"/> 2011/65/EU	Title: CAT 5E ASSEMBLED PATCH CABLE	
<small>This PROPRIETARY Document is property of Cinch Connectivity Solutions. It is confidential in nature, non-transferable, and issued with the clear understanding that it is not to be copied or retransmitted without permission and is returnable upon demand.</small>	<small>UNLESS OTHERWISE SPECIFIED UNITS: METRIC</small> .X ±.3 .XX ±.15 ANGLES ±2°	Model No. 73-777X-XXX	Date: 2015/8/4
<small>INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-2009.</small>	Size A	DO NOT SCALE DRAWING	Sheet 1 of 1