

Available in
500ft Spools

TRUE DMX 512

This cable features 4 conductors plus a ground, which makes it a true DMX 512 cable.

DOUBLE PROTECTION


Inside, this 4 conductor cable features both an aluminum and a braided shield which provides double the protection from EMI and cross talk.

FLEXIBLE PVC JACKET

This DMX cable comes complete with a matte PVC jacket that protects the interior workings of the cable from the harsh environment. It also helps the cable keep its shape for a perfect coil every time.

Product specifications may change without prior notification

Configuration



Product

Part number IO-D22428-500SP
 Number of Conductors 4 plus shield

Conductors

Details 20/0.12
 Size 24 AWG

Insulation

Material PE
 Colors Blue, White, Red, & Green

Shield

Material Tinned Copper & Aluminum
 Details Braided 16*9/0.10

Drain Wire

Material Tinned Copper
 Details 7/0.20

Jacket

O.D. 8.0mm
 Material PVC
 Color Black

Electrical and Mechanical Characteristics

Conductor DC Resistance ohm/1km	< 87.5
Shield DC Resistance ohm/1km	< 18.1
Voltage Breakdown	300V
Flex Life	> 58,800
Tensile Strength	> 745N
Applicable Temperature	-20°C ~ +60°C (-4°F ~ +140°F)
Peak Temperature	-40°C ~ +70°C (-40°F ~ +158°F)

PART NUMBER BREAKDOWN:

IO-A12326-500SP
 Type. "A" for Audio. "D" for Data

IO-A12326-500SP
 Number of Twisted Pairs

IO-A12326-500SP
 AWG Conductor Size

IO-A12326-500SP
 "1" for Spiral Shield. "2" for Braided Shield.

IO-A12326-500SP
 Outer Diameter. In mm.

IO-A12326-500SP
 500ft. Spool

Product specifications may change without prior notification

